

# Maxx® Slash® (Model 102076-4) Parts List

Parts shown in bold are optional accessories. Part categories and individual part listings are arranged alphabetically.

	Bearings & Bushings	10287
8799	Ball bearing kit, Maxx® (complete)	10287
8799X	Ball bearing kit, stainless steel, Maxx® (complete)	8987
5106A	Ball bearing, black rubber sealed (15x24x5mm) (2)	9627 10260
5107A	Ball Bearing, black rubber sealed (17x26x5) (2)	10200
5099A	Ball bearing, black rubber sealed (6x16x5mm) (2)	10263
2728	Ball bearings (5x8x2.5mm) (2)	10263
5119A	Ball bearings, black rubber sealed (10x15x4mm) (2)	10263
5120A 5101A	Ball bearings, black rubber sealed (12x18x4mm) (2) Ball bearings, black rubber sealed (12x21x5mm) (2)	10263
5098A	Ball bearings, black rubber sealed (12x21x5mm) (2)	10223
5180A	Ball bearings, black rubber sealed (6x13x5mm) (2)	9628
5118A	Ball bearings, black rubber sealed (8x16x5mm) (2)	8925
5101	Ball bearings, blue rubber sealed (12x21x5mm) (2)	8938) 8939)
7020	Ball bearings, blue rubber sealed (8x12x3.5mm) (2)	1024
	Body & Accessories	10244
10226	Body reinforcement set, black/ 3x10mm CS (8) (fits #10211 body)	7799
10224	Body reinforcement set, black/ skid pads (roof)/ 3x10mm CS (14) (fits #10211 body)	10278 7775
10216	Body reinforcement set, front (left & right) (attaches to #10211 body)	
10217	Body reinforcement set, rear (left & right) (attaches to #10211 body)	7775
0213	Body support (fits #10211 body)	
10219	Body support, side/ mount (left & right) (for #10211 body)	7775
0211	Body, Maxx Slash® (clear, requires painting)/ window masks/ decal sheet (includes body support, body plastics, latches, &	
	hardware for clipless mounting)	7775
0211R	Body, Maxx Slash® (clear, requires painting)/ window masks/ decal sheet (includes body support, body plastics, latches, &	
	hardware for clipless mounting) (heavy duty)	7775
10211-BLUE		
	body support, body plastics, & latches for clipless mounting)	77751
0211-GRN	Body, Maxx Slash®, green (painted)/ decal sheet (assembled with	7775
0044	body support, body plastics, & latches for clipless mounting)	
0211X	Body, Maxx Slash®, ProGraphix® (graphics are printed, requires paint & final color application)/ decal sheet (includes body	
	support, body plastics, latches, & hardware for clipless	6465
	mounting)	7793) 6442
0211-RED	Body, Maxx Slash®, red (painted)/ decal sheet (assembled with body	0442
	support, body plastics, & latches for clipless mounting)	6447F
0211-RNR	Body, Maxx Slash®, Rock n' Roll (painted)/ decal sheet (assembled with body support, body plastics, & latches for clipless mounting)	6443
0218	Latch, body mount (4) (for clipless body mounting) (attaches to	
0210	#10211 body)	6448F
10225	Skid pads (roof)/ retainers (2)/ 3x10mm CS (6) (fits #10211 body)	6444
	Bumpers & Skidplates	6449
10233	Bumper mount, front	
10235	Bumper, front	
0236	Bumper, rear	1028
0245	Skidplate, center/ 4x30 CCS (4)/ 3x10 CS (4)	
0244	Skidplate, front (1), rear (1)	8981
	Chassis & Attachments	1028
0215	Body mounts, front (left & right) (for clipless body mounting)	1028
0214	Body mounts, rear (left & right) (for clipless body mounting)	1020
0216	Body reinforcement set, front (left & right) (attaches to #10211 body)	5136
10217	Body reinforcement set, rear (left & right) (attaches to #10211 body)	80/0
3924	Box, receiver (sealed)/ wire cover/ foam pads/ silicone grease/ 2.5x10 CS (2)/ 3x10 CCS (3)	
0233	Bumper mount, front	1024
0235	Bumper, front	
0236	Bumper, rear	8991 8992
0222	Chassis	8992 8982
3921	Chassis brace, front	0002
	Chassis brace, front, 6061-T6 aluminum (blue-anodized/	8988
0221-BLUE	2.5x6mm CCS (with threadlock) (2)	5041
	2.5x6mm CCS (with threadlock) (2) Chassis brace, front, 6061-T6 aluminum (gray-anodized/	
0221-GRAY	Chassis brace, front, 6061-T6 aluminum (gray-anodized/ 2.5x6mm CCS (with threadlock) (2)	8985
0221-GRAY	Chassis brace, front, 6061-T6 aluminum (gray-anodized/ 2.5x6mm CCS (with threadlock) (2) Chassis brace, front, 6061-T6 aluminum (green-anodized/	8985 8986
10221-GRAY 10221-GRN	Chassis brace, front, 6061-T6 aluminum (gray-anodized/ 2.5x6mm CCS (with threadlock) (2) Chassis brace, front, 6061-T6 aluminum (green-anodized/ 2.5x6mm CCS (with threadlock) (2) Chassis brace, front, 6061-T6 aluminum (orange-anodized/	8985 8986 <b>5130</b> <b>5135</b>
10221-GRAY 10221-GRN 10221-ORNG	Chassis brace, front, 6061-T6 aluminum (gray-anodized/ 2.5x6mm CCS (with threadlock) (2) Chassis brace, front, 6061-T6 aluminum (green-anodized/ 2.5x6mm CCS (with threadlock) (2) Chassis brace, front, 6061-T6 aluminum (orange-anodized/ 2.5x6mm CCS (with threadlock) (2)	8985 8986 <b>5130</b> <b>5135</b> 5040
10221-GRAY 10221-GRN 10221-ORNG	Chassis brace, front, 6061-T6 aluminum (gray-anodized/ 2.5x6mm CCS (with threadlock) (2) Chassis brace, front, 6061-T6 aluminum (green-anodized/ 2.5x6mm CCS (with threadlock) (2) Chassis brace, front, 6061-T6 aluminum (orange-anodized/ 2.5x6mm CCS (with threadlock) (2) Chassis brace, front, 6061-T6 aluminum (red-anodized/ 2.5x6mm	8985 8986 <b>5130</b> <b>5135</b> 5040 <b>5136</b>
10221-GRAY 10221-GRN 10221-ORNG 10221-RED	Chassis brace, front, 6061-T6 aluminum (gray-anodized/ 2.5x6mm CCS (with threadlock) (2) Chassis brace, front, 6061-T6 aluminum (green-anodized/ 2.5x6mm CCS (with threadlock) (2) Chassis brace, front, 6061-T6 aluminum (orange-anodized/ 2.5x6mm CCS (with threadlock) (2) Chassis brace, front, 6061-T6 aluminum (red-anodized/ 2.5x6mm CCS (with threadlock) (2)	8985 8986 <b>5130</b> <b>5135</b> 5040 <b>5136</b> 5137
10221-GRAY 10221-GRN 10221-ORNG 10221-RED 10287-BLUE	Chassis brace, front, 6061-T6 aluminum (gray-anodized/ 2.5x6mm CCS (with threadlock) (2) Chassis brace, front, 6061-T6 aluminum (green-anodized/ 2.5x6mm CCS (with threadlock) (2) Chassis brace, front, 6061-T6 aluminum (orange-anodized/ 2.5x6mm CCS (with threadlock) (2) Chassis brace, front, 6061-T6 aluminum (red-anodized/ 2.5x6mm CCS (with threadlock) (2) Cover, gear (blue-anodized 6061-T6 aluminum)	8985 8986 <b>5130</b> <b>5135</b> 5040 <b>5136</b> 5137 8989 8978
10221-GRAY 10221-GRN 10221-ORNG 10221-RED 10287-BLUE	Chassis brace, front, 6061-T6 aluminum (gray-anodized/ 2.5x6mm CCS (with threadlock) (2) Chassis brace, front, 6061-T6 aluminum (green-anodized/ 2.5x6mm CCS (with threadlock) (2) Chassis brace, front, 6061-T6 aluminum (orange-anodized/ 2.5x6mm CCS (with threadlock) (2) Chassis brace, front, 6061-T6 aluminum (red-anodized/ 2.5x6mm CCS (with threadlock) (2)	8985 8986 <b>5130</b> <b>5135</b> 5040 <b>5136</b> 5137 8989

ranged alpha	betically.
287-ORNG	Cover, gear (orange-anodized 6061-T6 aluminum)
287-RED	Cover, gear (red-anodized 6061-T6 aluminum)
87	Covers, gear (2)
27	Hold down, battery
260	Motor mount cap
263-BLUE	Motor mount cap, 6061-T6 aluminum (blue-anodized)
263-GRAY	Motor mount cap, 6061-T6 aluminum (gray-anodized)
263-GRN	Motor mount cap, 6061-T6 aluminum (green-anodized)
263-ORNG	Motor mount cap, 6061-T6 aluminum (orange-anodized)
263-RED	Motor mount cap, 6061-T6 aluminum (red-anodized)
223	Nerf bars, chassis (2)
28	Retainer, battery hold-down (front and rear) (1 each)
25	Seal kit, receiver box (includes o-ring, seal, and silicone grease)
38X	Shock tower, front (left & right halves)
39X 245	Shock tower, rear (left & right halves) Skidplate, center/ 4x30 CCS (4)/ 3x10 CS (4)
244	Skidplate, front (1), rear (1)
99	Tires, rubber (2) (fits Traxxas® #7775X wheelie bar wheels)
278	Wheelie bar, assembled (fits Maxx® or Maxx Slash®)
75	Wheels, wheelie bar (2)/ axles, wheelie bar (2)/ 10x15x4 plastic
	bushings (4) (for #7776, 8976, or 9576 wheelie bar)
75X	Wheels, wheelie bar, 6061-T6 aluminum (blue-anodized) (2)/ axle,
754	wheelie bar, 6061-T6 aluminum (2)/ 10x15x4 ball bearings (4)
75A	Wheels, wheelie bar, 6061-T6 aluminum (dark titanium-anodized) (2)/ axle, wheelie bar, 6061-T6 aluminum (2)/ 10x15x4 ball
	bearings (4)
75G	Wheels, wheelie bar, 6061-T6 aluminum (green-anodized) (2)/
	axle, wheelie bar, 6061-T6 aluminum (2)/ 10x15x4 ball bearings
	(4)
75T	Wheels, wheelie bar, 6061-T6 aluminum (orange-anodized) (2)/
	axle, wheelie bar, 6061-T6 aluminum (2)/ 10x15x4 ball bearings
75R	(4) Wheels, wheelie bar, 6061-T6 aluminum (red-anodized) (2)/ axle,
/ JK	wheelie bar, 6061-T6 aluminum (2)/ 10x15x4 ball bearings (4)
05	Cush Drive Components
65 93X	Cush drive key/ pin/ elastomer damper
93A 42	Housing, cush drive (front & rear halves) Spur gear, 46-tooth (machined, hardened steel) (wide face, 1.0
	metric pitch)
47R	Spur gear, 46-tooth, steel (wide-face, 1.0 metric pitch)
43	Spur gear, 50-tooth (machined, hardened steel) (wide face, 1.0
	metric pitch)
48R	Spur gear, 50-tooth, steel (wide-face, 1.0 metric pitch)
44	Spur gear, 54-tooth (machined, hardened steel) (wide face, 1.0 metric pitch)
49R	Spur gear, 54-tooth, steel (wide-face, 1.0 metric pitch)
	Differential Components
281	Carrier, differential (aluminum)/ o-ring gaskets (2)/ ring gear gasket/
	spacers (4)/ 12.2x18x0.5 MW/ 3x15mm flat-head machine screws (with threadlock) (4)
81	Carrier, differential/ x-ring gasket/ o-ring (2)/ 10x19.5x0.5 TW
280A	Differential kit, center (complete) (aluminum carrier, 100K wt
	differential fluid) (fits Maxx® or Maxx® Slash®)
280X	Differential kit, center (complete) (aluminum carrier, 20MM wt
	differential fluid) (fits Maxx® or Maxx® Slash®)
36X	Differential oil kit (1 each: 10K, 30K, 50K weights)
49	Differential output yoke assembly, front or rear (assembled with external-splined half shaft)
249	Differential output yoke assembly, front or rear, Maxx® Duty steel
210	core (1) (assembled with external-splined half shaft)
91	Differential, front, complete (fits Maxx®)
92	Differential, rear, complete (fits Maxx®)
82	Gear set, differential (output gears (2)/ spider gears (4)/ spider gear
	shaft (2)/ output shaft (2)/ 2.5x13.8 pin (2))
88	Gear, center differential, 44-tooth
41	Grease, premium high performance (20cc)
85 86	Input gear, transmission, 22-tooth/ 2.5x12mm pin Input shaft, transmission
<b>30</b>	
	Oil, differential (100K wt) (0.7 oz (20cc))
35	Oil, differential (100K wt) (0.7 oz (20cc)) Oil, differential (10K wt) (1.7 oz (50cc))
	Oil, differential (100K wt) (0.7 oz (20cc)) Oil, differential (10K wt) (1.7 oz (50cc)) Oil, differential (20M wt) (standard)
<b>35</b> 40 <b>36</b>	Oil, differential (10K wt) (1.7 oz (50cc))
40 <b>36</b>	<b>Oil, differential (10K wt) (1.7 oz (50cc))</b> Oil, differential (20M wt) (standard)
40 <b>36</b> 37	<ul> <li>Oil, differential (10K wt) (1.7 oz (50cc))</li> <li>Oil, differential (20M wt) (standard)</li> <li>Oil, differential (30K wt) (1.7 oz (50cc))</li> <li>Oil, differential (50K wt) (1.7 oz (50cc))</li> <li>Output gear, center differential, hardened steel (2)</li> </ul>
40 36 37 89X 78	Oil, differential (10K wt) (1.7 oz (50cc)) Oil, differential (20M wt) (standard) Oil, differential (30K wt) (1.7 oz (50cc)) Oil, differential (50K wt) (1.7 oz (50cc)) Output gear, center differential, hardened steel (2) Ring gear, differential/ pinion gear, differential (front)
40	<ul> <li>Oil, differential (10K wt) (1.7 oz (50cc))</li> <li>Oil, differential (20M wt) (standard)</li> <li>Oil, differential (30K wt) (1.7 oz (50cc))</li> <li>Oil, differential (50K wt) (1.7 oz (50cc))</li> <li>Output gear, center differential, hardened steel (2)</li> </ul>

		Driveline Components	10297
	8952X	Carriers, stub axle (blue-anodized 6061-T6 aluminum) (rear) (2)	8958
	8952G	Carriers, stub axle (green-anodized 6061-T6 aluminum) (rear) (2)	
	8952	Carriers, stub axle (left & right)	40247 DI
	8952A	Carriers, stub axle (orange-anodized 6061-T6 aluminum) (rear)	10247-BL
		(2)	10247-GF
	8952R	Carriers, stub axle (red-anodized 6061-T6 aluminum) (rear) (2)	10247 01
	10249	Differential output yoke assembly, front or rear, Maxx® Duty steel	10247-GF
		core (1) (assembled with external-splined half shaft)	
	8951	Drive cup (1)/ 4x15.8mm screw pin (1) (for #8950X or 8996X steel	10247-OF
	9054	CV driveshafts)	
	8954 10250	Drive hub, front (1)/ 3x10 screw pin (1) Driveshaft assembly, front or rear, Maxx® Duty steel core (left or	10247-RE
	10230	right) (1) (fully assembled, ready to install)/ screw pin (1)	8947
	10255	Driveshaft, center, aluminum	0947
	8950A	Driveshaft, steel constant-velocity (shaft only, 89.5mm) (1) (for	8938X
		use only with #8951 drive cup)	10246-BL
	8950X	Driveshafts, steel constant-velocity (assembled), front or rear (4)	
		(#8654, 8654G, or 8654R and #7758, 7758G, or 7758R required for	
		a complete set)	
	8447A	Nuts, 5mm flanged nylon locking (aluminum, black-anodized,	
	0447V	serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, blue-anodized,	10246-GF
	8447X	serrated) (4)	
	8447G	Nuts, 5mm flanged nylon locking (aluminum, green-anodized,	
	01110	serrated) (4)	
	8447R	Nuts, 5mm flanged nylon locking (aluminum, red-anodized,	10246-GF
		serrated) (4)	
	8447	Nuts, 5mm flanged nylon locking (steel, black serrated) (8)	
	5040	Oil, differential (20M wt) (standard)	
	10253	Stub axle assembly, outer, Maxx® Duty (front or rear) (steel) (1)	10246-OF
	8956	Wheel hubs, hex (2)/ 2.5x14 pins (2)	10240-01
	8956X	Wheel hubs, hex, aluminum (blue-anodized) (4)/ 4x13mm screw	
	90560	pins (4) Wheel hube here elements (green energiand) (4) (4) 4:42 mm energy	
	8956G	Wheel hubs, hex, aluminum (green-anodized) (4)/ 4x13mm screw pins (4)	
	8956T	Wheel hubs, hex, aluminum (orange-anodized) (4)/ 4x13mm	10246-RE
	00001	screw pins (4)	
	8956R	Wheel hubs, hex, aluminum (red-anodized) (4)/ 4x13mm screw	
		pins (4)	
	8654	Wheel hubs, splined, 17mm (blue-anodized) (4)/ 4x5 GS (4),	8946
		3x14mm pin (4)	0010
	8654-GRAY	Wheel hubs, splined, 17mm (gray-anodized) (4)/ 4x5 GS (4),	8937X
	00540	3x14mm pin (4)	8937G
	8654G	Wheel hubs, splined, 17mm (green-anodized) (4)/ 4x5 GS (4),	8937A
	8654A	3x14mm pin (4) Wheel hubs, splined, 17mm (orange-anodized) (4)/ 4x5mm GS	
	0034A	(4)/ 3x14mm pin (4)	8937R
	8654R	Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4),	8937
		3x14mm pin (4)	10230
	8957	Wheel washers (4)	10230-BL
	10257	Wheel washers (4)	10230-GF
	8957X	Wheel washers, blue (4)	10230-OF
	8957G	Wheel washers, green (4)	10230-RE
	10257-BLUE	Wheel washers, machined aluminum, blue (4)	8929
	10257-GRAY	Wheel washers, machined aluminum, gray (4)	8929X 8929G
	10257-GRN	Wheel washers, machined aluminum, green (4)	8929G
		Wheel washers, machined aluminum, orange (4)	8929R
	10257-RED	Wheel washers, machined aluminum, red (4)	8929A
	8957T	Wheel washers, orange (4)	7743
r	8957R	Wheel washers, red (4)	7743-BLU
		Front Suspension & Steering	7743-GR/
1	8926	Bulkhead tie bar, front, upper (1)/ lower (2) (steel)	7743-GRI
	8920	Bulkhead, front (upper and lower)	7743-ORI
	8932X	Caster blocks (c-hubs), 6061-T6 aluminum (blue-anodized), left &	
		right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4)	7743-RE
	8932G	Caster blocks (c-hubs), 6061-T6 aluminum (green-anodized), left	8940X
		& right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4)	
	8932A	Caster blocks (c-hubs), 6061-T6 aluminum (orange-anodized),	8942
	8932R	left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (red-anodized), left &	JJ+2
	5352IX	right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4)	8941
	8932	Caster blocks (c-hubs), left & right	
		Draglink, steering, 6061-T6 aluminum (blue-anodized)	8940
		Draglink, steering, 6061-T6 aluminum (gray-anodized)	-
	10239-GRN	Draglink, steering, 6061-T6 aluminum (grep-anodized)	10295
		Draglink, steering, 6061-T6 aluminum (orange-anodized)	
	10239-RED	Draglink, steering, 6061-T6 aluminum (red-anodized)	10296
	10298	Linkage, sway bar (front or rear)	8948X
	8916	Mount, tie bar, front (1)/ rear (1)/ suspension pin retainer, front or rear	
		(2)	

iz Radio &	TSM® (Model 102076-4) Parts List
10297	Mounts, sway bar (front and rear)/ 3x6mm FCS (4)
8958	Rod ends (4) (assembled with steel pivot balls) (replacement
	ends for #8547A, 8547R, 8547X, 8948A, 8948G, 8948R, 8948X,
10247 BLUE	8997A, 8997G, 8997R, 8997X) Servo horn, steering, 6061-T6 aluminum (blue-anodized)/
10247-BLOE	3x15mm BCS (with threadlock) (1)
10247-GRAY	Servo horn, steering, 6061-T6 aluminum (gray-anodized)/
	3x15mm BCS (with threadlock) (1)
10247-GRN	Servo horn, steering, 6061-T6 aluminum (green-anodized)/
10247-ORNG	3x15mm BCS (with threadlock) (1) Servo horn, steering, 6061-T6 aluminum (orange-anodized)/
	3x15mm BCS (with threadlock) (1)
10247-RED	Servo horn, steering, 6061-T6 aluminum (red-anodized)/ 3x15mm
2047	BCS (with threadlock) (1)
3947	Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls)
3938X	Shock tower, front (left & right halves)
10246-BLUE	Steering bellcranks, draglink (blue-anodized 6061-T6 aluminum)/
	bellcrank bushing (1)/ 3x20mm BCS (with threadlock) (2)/ 3x20mm BCS (with threadlock) (2)/ 3x20mm shoulder screws
	(with threadlock) (2)/ 3x15mm BCS (with threadlock) (1)/ 3x10mm
	CS (with threadlock) (1)
10246-GRAY	Steering bellcranks, draglink (gray-anodized 6061-T6 aluminum)/
	bellcrank bushing (1)/ 3x20mm BCS (with threadlock) (2)/ 3x20mm BCS (with threadlock) (2)/ 3x20mm shoulder screws
	(with threadlock) (2)/ 3x15mm BCS (with threadlock) (1)/ 3x10mm
	CS (with threadlock) (1)
10246-GRN	Steering bellcranks, draglink (green-anodized 6061-T6 aluminum)/ bellcrank bushing (1)/ 3x20mm BCS (with threadlock)
	(2)/ 3x20mm BCS (with threadlock) (2)/ 3x20mm shoulder screws
	(with threadlock) (2)/ 3x15mm BCS (with threadlock) (1)/ 3x10mm
	CS (with threadlock) (1)
10246-ORNG	Steering bellcranks, draglink (orange-anodized 6061-T6 aluminum)/ bellcrank bushing (1)/ 3x20mm BCS (with threadlock)
	(2)/ 3x20mm BCS (with threadlock) (2)/ 3x20mm shoulder screws
	(with threadlock) (2)/ 3x15mm BCS (with threadlock) (1)/ 3x10mm
10246-RED	CS (with threadlock) (1) Steering bellcranks, draglink (red-anodized 6061-T6 aluminum)/
	bellcrank bushing (1)/ 3x20mm BCS (with threadlock) (2)/
	3x20mm BCS (with threadlock) (2)/ 3x20mm shoulder screws
	(with threadlock) (2)/ 3x15mm BCS (with threadlock) (1)/ 3x10mm CS (with threadlock) (1)
3946	Steering bellcranks/ bellcrank support/ servo saver/ servo saver
	spring/ draglink/ 3x20mm shoulder screws (2)
3937X	Steering blocks, 6061-T6 aluminum (blue-anodized), left & right
3937G 3937A	Steering blocks, 6061-T6 aluminum (green-anodized), left & right Steering blocks, 6061-T6 aluminum (orange-anodized), left &
5351 A	right
3937R	Steering blocks, 6061-T6 aluminum (red-anodized), left & right
3937	Steering blocks, left & right
10230	Suspension arms, lower, black (left and right, front or rear) (2) Suspension arms, lower, blue (left and right, front or rear) (2)
10230-GRN	Suspension arms, lower, green (left and right, front or rear) (2)
	Suspension arms, lower, orange (left and right, front or rear) (2)
10230-RED	Suspension arms, lower, red (left and right, front or rear) (2)
3929	Suspension arms, upper, black (left or right, front or rear) (2)
3929X 3929G	Suspension arms, upper, blue (left or right, front or rear) (2) Suspension arms, upper, green (left or right, front or rear) (2)
8929T	Suspension arms, upper, orange (left or right, front or rear) (2)
8929R	Suspension arms, upper, red (left or right, front or rear) (2)
3929A	Suspension arms, upper, white (left or right, front or rear) (2)
7743 7743 DI UE	Suspension pin retainer (4)
7743-BLUE 7743-GRAY	Suspension pin retainer, 6061-T6 aluminum (blue-anodized) (4) Suspension pin retainer, 6061-T6 aluminum (gray-anodized) (4)
7743-GRN	Suspension pin retainer, 6061-T6 aluminum (gray-unodized) (4)
7743-ORNG	Suspension pin retainer, 6061-T6 aluminum (orange-anodized)
	(4)
7743-RED 3940X	Suspension pin retainer, 6061-T6 aluminum (red-anodized) (4) Suspension pin set, complete (hardened steel), 4x64mm (4),
55407	4x22mm (4), 4x38mm (4), 4x33mm (4), 4x47mm (4)/ 3x8mm BCS
	(14)/ 3x6mm BCS (4)/ retainers (8)
3942	Suspension pin set, front (left or right) (hardened steel), 4x64mm
3941	(1), 4x22mm (2), 4x38mm (1), 4x33mm (1), 4x47mm (1) Suspension pins, lower, inner (front or rear), 4x64mm (2) (hardened
	steel)
3940	Suspension screw pin set, front or rear (hardened steel), 4x18mm (4),
10295	4x38mm (2), 4x33mm (2), 4x43mm (2) Sway bar kit, Maxx Slash® (front and rear) (includes front and
	rear sway bars and linkage)
10296	Sway bar set, Maxx Slash® (includes 1 each of all 5 sway bars)
3948X	Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/rod ands rear (4)/rod ands
	stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1)

#### Page 3 Maxx® Slash®: TQi™ Traxxas Link™ Enabled 2.4GHz Radio & TSM® (Model 102076-4) Parts List

	Page 3 I	Naxx® Siasn®: IQI'" Iraxxas Link'" Enabled 2.4G	nz kac
	8948-GRAY	Toe links, front (TUBES gray-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1)	10263-0 10263-F 10262-E
	8948G	Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1)	
	8948A	Toe links, front (TUBES orange-anodized, 7075-T6 aluminum,	10262-0
	8948R	stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES red-anodized, 7075-T6 aluminum,	10262-0
		stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1)	40262 0
1			10262-0
		Hardware	
	1552	3x8mm Hex Cap Screws (6)/ Washers (6)/ Wrench (1)	10262-F
	3642	Attachment screws, shock (3x12mm shoulder screws) (6)	
	4859	CS 3x10 flathead (hex drive)	
	2584	Head screws, 3x12mm cap-head machine (hex drive) (6) (TRX® 2.5, 2.5R, 3.3)	8960
	8447A	Nuts, 5mm flanged nylon locking (aluminum, black-anodized, serrated) (4)	8960X
	8447X	Nuts, 5mm flanged nylon locking (aluminum, blue-anodized, serrated) (4)	3483
	8447G	Nuts, 5mm flanged nylon locking (aluminum, green-anodized, serrated) (4)	3483R
	8447R	Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4)	
	8447	Nuts, 5mm flanged nylon locking (steel, black serrated) (8)	2091
	5147X	Nuts, 5mm flanged nylon locking (steel, serrated) (8)	8947X
	3236	Screws, 2.5x12mm cap-head machine (6)	10247-E
	2577	Screws, 3x10mm button-head machine (hex drive) (6)	
	2587	Screws, 3x10mm caphead machine (6) (no washer)	10247-0
	2551	Screws, 3x10mm countersunk machine (6) (hex drive)	
	2578	Screws, 3x12mm button-head machine (hex drive) (6)	10247-0
	2579	Screws, 3x15mm button-head machine (hex drive) (6)	
	2553	Screws, 3x15mm countersunk machine (6) (hex drive)	10247-C
	3646	Screws, 3x15mm flat-head machine (hex drive) (6)	40047 5
	2583	Screws, 3x18 button-head machine (hex drive) (6)	10247-F
	2581	Screws, 3x25mm button-head machine (hex drive) (6)	8947
	2582	Screws, 3x30mm button-head machine (hex drive) (6)	0947
	2657	Screws, 3x8mm caphead machine (hex drive) (6)	2090
	2550	Screws, 3x8mm countersunk machine (6) (hex drive)	2085
	3936	Screws, 4x10mm button-head machine (hex drive) (6)	2085X
	2535	Screws, 4x10mm countersunk machine (hex drive) (6)	2000/1
	3937	Screws, 4x12mm button-head machine (hex drive) (6)	2085R
	3938	Screws, 4x14mm button-head machine (hex drive) (6)	
	3933	Screws, 4x16mm button-head machine (hex drive) (6)	3484
	2589	Screws, 4x20mm button-head machine (hex drive) (6) Screws, 4x24mm button-head machine (hex drive) (6)	
	2455 2596	Screws, 4x25mm button-head machine (hex drive) (6)	3485T
	2590	Screws, 4x25mm button-head machine (hex drive) (6)	
		Suspension pin set, complete (hardened steel), 4x64mm (4),	
	8940X	4x22mm (4), 4x38mm (4), 4x33mm (4), 4x47mm (4)/ 3x8mm BCS	2872X
		(14)/ 3x6mm BCS (4)/ retainers (8)	2889X
	8942	Suspension pin set, front (left or right) (hardened steel), 4x64mm	2003A 2857¥
		(1), 4x22mm (2), 4x38mm (1), 4x33mm (1), 4x47mm (1)	2914
	8943	Suspension pin set, rear (left or right) (hardened steel), 4x64mm	
		(1), 4x38mm (1), 4x33mm (1), 4x47mm (1)	20007
		LED Lights	1926
	6500	High-Voltage Power Amplifier	1726
	6590		1726A
	7884	LED light bar, front (high-voltage) (40 white LEDs (double row), 82mm wide) (fits Maxx®, X-Maxx®, or XRT™)	2943
	7883X	LED light bar, rear, red (with white reverse light) (high-voltage)	6548
	10037	(24 red LEDs, 24 white LEDs, 100mm wide)/ light bar mount (fits	
		Maxx®, Maxx Slash®, X-Maxx®, or XRT™)	2990
	10290	LED light kit, Maxx Slash®, complete (includes #6590 high-	
		voltage power amplifier)	2972
		Motors & Electronics	2973
	7749	Adapter, standard servo (adapts standard servo to fit in X- Maxx®)Adapter, standard servo (adapts standard servo to fit in	2970
	10287-BLUE	Maxx®, X-Maxx®, or XRT®) Cover, gear (blue-anodized 6061-T6 aluminum)	2981
		Cover, gear (gray-anodized 6061-T6 aluminum)	
	10287-GRN	Cover, gear (green-anodized 6061-T6 aluminum)	6525
		Cover, gear (orange-anodized 6061-T6 aluminum)	6525
	10287-RED	Cover, gear (red-anodized 6061-T6 aluminum)	8527
	8987	Covers, gear (2)	
	2092	Gear set (for 2090 servo)	2971
	10260	Motor mount cap	2000
		Motor mount cap, 6061-T6 aluminum (blue-anodized)	2092 <b>2968X</b>
		Motor mount cap, 6061-T6 aluminum (gray-anodized)	7200Y
	10263-GRN	Motor mount cap, 6061-T6 aluminum (green-anodized)	

0263-ORNG	Motor mount cap, 6061-T6 aluminum (orange-anodized)
0263-RED	Motor mount cap, 6061-T6 aluminum (red-anodized)
0262-BLUE	Motor mounts (front & rear) (blue-anodized 6061-T6 aluminum)/
	3x10mm CCS (with threadlock) (4)/ 4x12mm BCS (with
	threadlock) (2) (for use with #3483 motor)
0262-GRAY	Motor mounts (front & rear) (gray-anodized 6061-T6 aluminum)/
	3x10mm CCS (with threadlock) (4)/ 4x12mm BCS (with threadlock) (2) (for use with #3483 motor)
0262-GRN	Motor mounts (front & rear) (green-anodized 6061-T6 aluminum)/
	3x10mm CCS (with threadlock) (4)/ 4x12mm BCS (with
	threadlock) (2) (for use with #3483 motor)
0262-ORNG	Motor mounts (front & rear) (orange-anodized 6061-T6
	aluminum)/ 3x10mm CCS (with threadlock) (4)/ 4x12mm BCS
	(with threadlock) (2) (for use with #3483 motor)
0262-RED	Motor mounts (front & rear) (red-anodized 6061-T6 aluminum)/
	3x10mm CCS (with threadlock) (4)/ 4x12mm BCS (with threadlock) (2) (for use with #3483 motor)
960	Motor mounts (front and rear)/ 4x10 BCS with split and flat washers
	(1)/ pin (1)
960X	Motor mounts (front and rear)/ 4x10 BCS with split and flat
	washers (1)/ pin (1) (for installation of #3481 motor into Maxx®)
483	Motor, 2000Kv 77mm, brushless (with 6.5mm gold-plated connectors
	& high-efficiency heatsink)
483R	Rebuild kit, 2000Kv motor, brushless (includes plastic endbell,
	5x16x5mm ball bearings (2), 5.05x7.5x.05 washer (1), 5.05x7.5x0.1 washer (1), 5.05x7.5x.19 washer (1), 6x5x8.5 spacer
	(1))
091	Servo case/ gaskets (for 2090 waterproof servo)
947X	Servo horn, steel
0247-BLUE	Servo horn, steering, 6061-T6 aluminum (blue-anodized)/
	3x15mm BCS (with threadlock) (1)
0247-GRAY	Servo horn, steering, 6061-T6 aluminum (gray-anodized)/
	3x15mm BCS (with threadlock) (1)
0247-GRN	Servo horn, steering, 6061-T6 aluminum (green-anodized)/ 3x15mm BCS (with threadlock) (1)
0247-ORNG	Servo horn, steering, 6061-T6 aluminum (orange-anodized)/
0247-01110	3x15mm BCS (with threadlock) (1)
0247-RED	Servo horn, steering, 6061-T6 aluminum (red-anodized)/ 3x15mm
	BCS (with threadlock) (1)
947	Servo horn, steering/ linkage, steering (46mm, assembled with pivot
	balls)
090	Servo, digital high-torque (ball bearing), waterproof
085	Servo, digital high-torque (ball bearing), waterproof
085X	Servo, digital high-torque, metal gear (ball bearing), waterproof/ servo saver spring/ steering link
085R	Servo, digital high-torque/high-speed, metal gear (ball bearing),
	waterproof
484	Velineon® VXL-6s Brushless Power System, waterproof (includes
	VXL-6s ESC and 2000Kv, 77mm motor)
485T	Velineon® VXL-6s Electronic Speed Control, waterproof (brushless)
	(fwd/rev/brake)
	Radio System, Batteries & Chargers
872X	5000mah 11.1v 3-Cell 25C LiPo Battery
889X	5000mah 14.8v 4-Cell 25C LiPo Battery (long)
857X	6400mah 11.1v 3-Cell 25C LiPo Battery
914	AA 4PK
938X	Adapter, Traxxas® iD® LiPo battery (adapts Traxxas® iD®
200	batteries to separate balance ports)
926 <b>726</b>	Antenna caps, vinyl (2)/ antenna spool Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1)
726A	
	Antenna, tube, black (1)/ vinyl antenna cap (1)/ wire retainer (1) Battery charge indicators, green (4), grey (4), blue (4)
943	Battery charge indicators, green (4), grey (4), blue (4)
943	<b>Battery charge indicators, green (4), grey (4), blue (4)</b> Battery door, TQ 2.4 transmitter (replacement for #6516, 6517
<b>943</b> 548	Battery charge indicators, green (4), grey (4), blue (4) Battery door, TQ 2.4 transmitter (replacement for #6516, 6517 transmitter)
<b>943</b> 548	Battery charge indicators, green (4), grey (4), blue (4) Battery door, TQ 2.4 transmitter (replacement for #6516, 6517 transmitter) Battery/charger completer pack (includes #2972 Dual iD charger (1), #2872X 5000mAh 11.1V 3-cell 25C LiPo iD® Battery (2)) Charger, EZ-Peak Dual, 100W, NiMH/LiPo with iD Auto Battery
943 548 990 972	Battery charge indicators, green (4), grey (4), blue (4) Battery door, TQ 2.4 transmitter (replacement for #6516, 6517 transmitter) Battery/charger completer pack (includes #2972 Dual iD charger (1), #2872X 5000mAh 11.1V 3-cell 25C LiPo iD® Battery (2)) Charger, EZ-Peak Dual, 100W, NiMH/LiPo with iD Auto Battery Identification
943 548 990	Battery charge indicators, green (4), grey (4), blue (4) Battery door, TQ 2.4 transmitter (replacement for #6516, 6517 transmitter) Battery/charger completer pack (includes #2972 Dual iD charger (1), #2872X 5000mAh 11.1V 3-cell 25C LiPo iD® Battery (2)) Charger, EZ-Peak Dual, 100W, NiMH/LiPo with iD Auto Battery Identification Charger, EZ-Peak Live Dual, 200W, NiMH/LiPo with iD Auto
943 548 990 972 973	Battery charge indicators, green (4), grey (4), blue (4) Battery door, TQ 2.4 transmitter (replacement for #6516, 6517 transmitter) Battery/charger completer pack (includes #2972 Dual iD charger (1), #2872X 5000mAh 11.1V 3-cell 25C LiPo iD® Battery (2)) Charger, EZ-Peak Dual, 100W, NiMH/LiPo with iD Auto Battery Identification Charger, EZ-Peak Live Dual, 200W, NiMH/LiPo with iD Auto Battery Identification
943 548 990 972	Battery charge indicators, green (4), grey (4), blue (4) Battery door, TQ 2.4 transmitter (replacement for #6516, 6517 transmitter) Battery/charger completer pack (includes #2972 Dual iD charger (1), #2872X 5000mAh 11.1V 3-cell 25C LiPo iD® Battery (2)) Charger, EZ-Peak Dual, 100W, NiMH/LiPo with iD Auto Battery Identification Charger, EZ-Peak Live Dual, 200W, NiMH/LiPo with iD Auto Battery Identification Charger, EZ-Peak Plus, 4 amp, NiMH/LiPo with iD Auto Battery
943 548 990 972 973	Battery charge indicators, green (4), grey (4), blue (4) Battery door, TQ 2.4 transmitter (replacement for #6516, 6517 transmitter) Battery/charger completer pack (includes #2972 Dual iD charger (1), #2872X 5000mAh 11.1V 3-cell 25C LiPo iD® Battery (2)) Charger, EZ-Peak Dual, 100W, NiMH/LiPo with iD Auto Battery Identification Charger, EZ-Peak Live Dual, 200W, NiMH/LiPo with iD Auto Battery Identification Charger, EZ-Peak Plus, 4 amp, NiMH/LiPo with iD Auto Battery Identification
943 548 990 972 973 970	Battery charge indicators, green (4), grey (4), blue (4) Battery door, TQ 2.4 transmitter (replacement for #6516, 6517 transmitter) Battery/charger completer pack (includes #2972 Dual iD charger (1), #2872X 5000mAh 11.1V 3-cell 25C LiPo iD® Battery (2)) Charger, EZ-Peak Dual, 100W, NiMH/LiPo with iD Auto Battery Identification Charger, EZ-Peak Live Dual, 200W, NiMH/LiPo with iD Auto Battery Identification Charger, EZ-Peak Plus, 4 amp, NiMH/LiPo with iD Auto Battery
943 548 990 972 973 970	Battery charge indicators, green (4), grey (4), blue (4) Battery door, TQ 2.4 transmitter (replacement for #6516, 6517 transmitter) Battery/charger completer pack (includes #2972 Dual iD charger (1), #2872X 5000mAh 11.1V 3-cell 25C LiPo iD® Battery (2)) Charger, EZ-Peak Dual, 100W, NiMH/LiPo with iD Auto Battery Identification Charger, EZ-Peak Live Dual, 200W, NiMH/LiPo with iD Auto Battery Identification Charger, EZ-Peak Plus, 4 amp, NiMH/LiPo with iD Auto Battery Identification Charger, EZ-Peak® Plus 4s, 8 amp, NiMH/LiPo with iD® Auto
943 548 9990 972 973 970 981	Battery charge indicators, green (4), grey (4), blue (4) Battery door, TQ 2.4 transmitter (replacement for #6516, 6517 transmitter) Battery/charger completer pack (includes #2972 Dual iD charger (1), #2872X 5000mAh 11.1V 3-cell 25C LiPo iD® Battery (2)) Charger, EZ-Peak Dual, 100W, NiMH/LiPo with iD Auto Battery Identification Charger, EZ-Peak Live Dual, 200W, NiMH/LiPo with iD Auto Battery Identification Charger, EZ-Peak Plus, 4 amp, NiMH/LiPo with iD Auto Battery Identification Charger, EZ-Peak Plus, 4 amp, NiMH/LiPo with iD Auto Battery Identification Charger, EZ-Peak® Plus 4s, 8 amp, NiMH/LiPo with iD® Auto Battery Identification
943 548 9990 972 973 970 981 525	Battery charge indicators, green (4), grey (4), blue (4) Battery door, TQ 2.4 transmitter (replacement for #6516, 6517 transmitter) Battery/charger completer pack (includes #2972 Dual iD charger (1), #2872X 5000mAh 11.1V 3-cell 25C LiPo iD® Battery (2)) Charger, EZ-Peak Dual, 100W, NiMH/LiPo with iD Auto Battery Identification Charger, EZ-Peak Live Dual, 200W, NiMH/LiPo with iD Auto Battery Identification Charger, EZ-Peak Plus, 4 amp, NiMH/LiPo with iD Auto Battery Identification Charger, EZ-Peak® Plus 4s, 8 amp, NiMH/LiPo with iD & Auto Battery Identification Charger, EZ-Peak® Plus 4s, 8 amp, NiMH/LiPo with iD® Auto Battery Identification Communication link, telemetry expander Communication link, telemetry expander Connector, 25.2 volt to 14.8 volt jumper (allows a Traxxas® dual-
943 548 990 972 973 970 981 525 525 527	Battery charge indicators, green (4), grey (4), blue (4) Battery door, TQ 2.4 transmitter (replacement for #6516, 6517 transmitter) Battery/charger completer pack (includes #2972 Dual iD charger (1), #2872X 5000mAh 11.1V 3-cell 25C LiPo iD® Battery (2)) Charger, EZ-Peak Dual, 100W, NiMH/LiPo iD® Battery (2)) Charger, EZ-Peak Live Dual, 200W, NiMH/LiPo with iD Auto Battery Identification Charger, EZ-Peak Live Dual, 200W, NiMH/LiPo with iD Auto Battery Identification Charger, EZ-Peak Plus, 4 amp, NiMH/LiPo with iD Auto Battery Identification Charger, EZ-Peak® Plus 4s, 8 amp, NiMH/LiPo with iD® Auto Battery Identification Communication link, telemetry expander Communication link, telemetry expander Connector, 25.2 volt to 14.8 volt jumper (allows a Traxxas® dual- battery 25.2 ESC to run on a single 14.8V battery pack)
943 548 990 972 973 970 981 525 525	Battery charge indicators, green (4), grey (4), blue (4) Battery door, TQ 2.4 transmitter (replacement for #6516, 6517 transmitter) Battery/charger completer pack (includes #2972 Dual iD charger (1), #2872X 5000mAh 11.1V 3-cell 25C LiPo iD® Battery (2)) Charger, EZ-Peak Dual, 100W, NiMH/LiPo with iD Auto Battery Identification Charger, EZ-Peak Live Dual, 200W, NiMH/LiPo with iD Auto Battery Identification Charger, EZ-Peak Plus, 4 amp, NiMH/LiPo with iD Auto Battery Identification Charger, EZ-Peak® Plus 4s, 8 amp, NiMH/LiPo with iD® Auto Battery Identification Charger, EZ-Peak® Plus 4s, 8 amp, NiMH/LiPo with iD® Auto Battery Identification Communication link, telemetry expander Communication link, telemetry expander Connector, 25.2 volt to 14.8 volt jumper (allows a Traxxas® dual- battery 25.2 ESC to run on a single 14.8V battery pack) EZ-Peak Live 12-amp NiMH/LiPo Fast Charger with iD® Auto
943 548 9990 972 973 970 981 525 527 527 971	Battery charge indicators, green (4), grey (4), blue (4) Battery door, TQ 2.4 transmitter (replacement for #6516, 6517 transmitter) Battery/charger completer pack (includes #2972 Dual iD charger (1), #2872X 5000mAh 11.1V 3-cell 25C LiPo iD® Battery (2)) Charger, EZ-Peak Dual, 100W, NiMH/LiPo with iD Auto Battery Identification Charger, EZ-Peak Live Dual, 200W, NiMH/LiPo with iD Auto Battery Identification Charger, EZ-Peak Plus, 4 amp, NiMH/LiPo with iD Auto Battery Identification Charger, EZ-Peak® Plus 4s, 8 amp, NiMH/LiPo with iD & Auto Battery Identification Charger, EZ-Peak® Plus 4s, 8 amp, NiMH/LiPo with iD® Auto Battery Identification Communication link, telemetry expander Communication link, telemetry expander Connector, 25.2 volt to 14.8 volt jumper (allows a Traxxas® dual- battery 25.2 ESC to run on a single 14.8V battery pack) EZ-Peak Live 12-amp NiMH/LiPo Fast Charger with iD® Auto Battery Identification and Bluetooth®
943 548 990 972 973 970 981 525 525 527 971	Battery charge indicators, green (4), grey (4), blue (4) Battery door, TQ 2.4 transmitter (replacement for #6516, 6517 transmitter) Battery/charger completer pack (includes #2972 Dual iD charger (1), #2872X 5000mAh 11.1V 3-cell 25C LiPo iD® Battery (2)) Charger, EZ-Peak Dual, 100W, NiMH/LiPo with iD Auto Battery Identification Charger, EZ-Peak Live Dual, 200W, NiMH/LiPo with iD Auto Battery Identification Charger, EZ-Peak Plus, 4 amp, NiMH/LiPo with iD Auto Battery Identification Charger, EZ-Peak® Plus 4s, 8 amp, NiMH/LiPo with iD & Auto Battery Identification Charger, EZ-Peak® Plus 4s, 8 amp, NiMH/LiPo with iD® Auto Battery Identification Communication link, telemetry expander Communication link, telemetry expander Connector, 25.2 volt to 14.8 volt jumper (allows a Traxxas® dual- battery 25.2 ESC to run on a single 14.8V battery pack) EZ-Peak Live 12-amp NiMH/LiPo Fast Charger with iD® Auto Battery Identification and Bluetooth® Gear set (for 2090 servo)
943 548 9990 972 973 970 981 525 527 527 971	Battery charge indicators, green (4), grey (4), blue (4) Battery door, TQ 2.4 transmitter (replacement for #6516, 6517 transmitter) Battery/charger completer pack (includes #2972 Dual iD charger (1), #2872X 5000mAh 11.1V 3-cell 25C LiPo iD® Battery (2)) Charger, EZ-Peak Dual, 100W, NiMH/LiPo with iD Auto Battery Identification Charger, EZ-Peak Live Dual, 200W, NiMH/LiPo with iD Auto Battery Identification Charger, EZ-Peak Plus, 4 amp, NiMH/LiPo with iD Auto Battery Identification Charger, EZ-Peak® Plus, 4 amp, NiMH/LiPo with iD Auto Battery Identification Charger, EZ-Peak® Plus 4s, 8 amp, NiMH/LiPo with iD® Auto Battery Identification Charger, EZ-Peak® Plus 4s, 8 amp, NiMH/LiPo with iD® Auto Battery Identification Communication link, telemetry expander Connector, 25.2 volt to 14.8 volt jumper (allows a Traxxas® dual- battery 25.2 ESC to run on a single 14.8V battery pack) EZ-Peak Live 12-amp NiMH/LiPo Fast Charger with iD® Auto Battery Identification and Bluetooth® Gear set (for 2090 servo) LiPo cell voltage checker/balancer (includes #2938X adapter for
943 548 990 972 973 970 981 525 525 527 971	Battery charge indicators, green (4), grey (4), blue (4) Battery door, TQ 2.4 transmitter (replacement for #6516, 6517 transmitter) Battery/charger completer pack (includes #2972 Dual iD charger (1), #2872X 5000mAh 11.1V 3-cell 25C LiPo iD® Battery (2)) Charger, EZ-Peak Dual, 100W, NiMH/LiPo with iD Auto Battery Identification Charger, EZ-Peak Live Dual, 200W, NiMH/LiPo with iD Auto Battery Identification Charger, EZ-Peak Plus, 4 amp, NiMH/LiPo with iD Auto Battery Identification Charger, EZ-Peak® Plus 4s, 8 amp, NiMH/LiPo with iD® Auto Battery Identification Charger, EZ-Peak® Plus 4s, 8 amp, NiMH/LiPo with iD® Auto Battery Identification Communication link, telemetry expander Commenciation link, telemetry expander Connector, 25.2 volt to 14.8 volt jumper (allows a Traxxas® dual- battery 25.2 ESC to run on a single 14.8V battery pack) EZ-Peak Live 12-amp NiMH/LiPo Fast Charger with iD® Auto Battery Identification and Bluetooth® Gear set (for 2090 servo)

#### Page 4 Maxx® Slash®: TQi™ Traxxas Link™ Enabled 2.4GHz Radio & TSM® (Model 102076-4) Parts List

Page 4 N	naxx® Siasn®: TQI Traxxas Link Enabled 2.40	
2968	LiPo cell voltage checker/balancer (requires #2938X adapter for Traxxas® iD® batteries)	
6535	Mount, temperature sensor (electric motors)/ wire tie/ thermal	5031 5032
	pad	5032
6533	Receiver, micro, TQi 2.4GHz with telemetry & TSM® (5-channel)	5033 5034
6552	Seal kit, expander box (includes o-ring, seals, and silicone	5034 5035
6506	grease)	5036
6526	Sensor, auto-detectable, temperature	5030
6527	Sensor, auto-detectable, voltage	5029
6521	Servo case/ gaskets (for 2090 waterproof servo)	5038X
2091	5 ( 1 )	JUJUX
2090 6553X	Servo, digital high-torque (ball bearing), waterproof Telemetry Expander 2.0 and GPS module 2.0, TQi radio system	5038
6550X	Telemetry expander 2.0, TQi radio system (for use only with	
00000	#6551X GPS module)	
6551X	Felemetry GPS module 2.0, TQi radio system (for use only with #6550X telemetry expander)	8965X 8965G
6509R	TQi 2.4 GHz High Output radio system, 2-channel, Traxxas® Link	8965T 8965R
6507D	enabled, TSM® (2-ch transmitter, 5-ch micro receiver) TQi 2.4 GHz High Output radio system, 4-channel with Traxxas®	8962
6507R	Link Bluetooth® module, TSM® (4-ch transmitter, 5-ch micro receiver)	8964X
6528	Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 2-	8964-G
0520	channel (transmitter only)	8964G
6529	Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 3-	8964T
0025	channel (transmitter only)	8964R
6530	Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 4-	8964
	channel (transmitter only)	
6511	Traxxas® Link Bluetooth® module	8963
	Ready-To-Race Model	<del>.</del>
102076-4	Maxx® Slash®: 1/10 Scale 4WD Brushless Electric Short Course	8963T
102070-4	Racing Truck with TQi™ Traxxas Link™ Enabled 2.4GHz Radio	9660
	System & Traxxas Stability Management (TSM)®	
	Rear Suspension	8961G
8927 8928	Bulkhead tie bar, rear, upper (1)/ lower front (1)/ lower rear (1) (steel) Bulkhead, rear (upper and lower)	8961T
8952X 8952G	Carriers, stub axle (blue-anodized 6061-T6 aluminum) (rear) (2) Carriers, stub axle (green-anodized 6061-T6 aluminum) (rear) (2)	8961R
8952	Carriers, stub axle (left & right)	0000V
8952A	Carriers, stub axle (orange-anodized 6061-T6 aluminum) (rear) (2)	8968X
8952R	Carriers, stub axle (red-anodized 6061-T6 aluminum) (rear) (2)	8968-G
10298	Linkage, sway bar (front or rear)	8968G
8916	Mount, tie bar, front (1)/ rear (1)/ suspension pin retainer, front or rear (2)	8968A
10297	Mounts, sway bar (front and rear)/ 3x6mm FCS (4)	000071
8958	Rod ends (4) (assembled with steel pivot balls) (replacement ends for #8547A, 8547R, 8547X, 8948A, 8948G, 8948R, 8948X,	8968R
	8997A, 8997G, 8997R, 8997X)	10240
10234	Shock mount, lower (extended travel, left & right/ 3x18mm BCS (2)	10241
8939X 10230	Shock tower, rear (left & right halves) Suspension arms, lower, black (left and right, front or rear) (2)	10242
10230-BLUE		
10230-GRN	Suspension arms, lower, green (left and right, front or rear) (2)	10243
10230-OKNG	Suspension arms, lower, orange (left and right, front or rear) (2) Suspension arms, lower, red (left and right, front or rear) (2)	
8929 <b>8929X</b>	Suspension arms, upper, black (left or right, front or rear) (2) Suspension arms, upper, blue (left or right, front or rear) (2)	6487X
8929G	Suspension arms, upper, green (left or right, front or rear) (2)	
8929T	Suspension arms, upper, orange (left or right, front or rear) (2)	6489X
8929R	Suspension arms, upper, red (left or right, front or rear) (2)	6400Y
8929A	Suspension arms, upper, white (left or right, front or rear) (2)	6490X
7743	Suspension pin retainer (4)	6491X
7743-BLUE	Suspension pin retainer, 6061-T6 aluminum (blue-anodized) (4)	••••
7743-GRAY	Suspension pin retainer, 6061-T6 aluminum (gray-anodized) (4)	6491R
7743-GRN	Suspension pin retainer, 6061-T6 aluminum (green-anodized) (4)	
7743-ORNG	Suspension pin retainer, 6061-T6 aluminum (orange-anodized) (4)	6494X
7743-RED	Suspension pin retainer, 6061-T6 aluminum (red-anodized) (4)	6495X
8940X	Suspension pin set, complete (hardened steel), 4x64mm (4),	04908
	4x22mm (4), 4x38mm (4), 4x33mm (4), 4x47mm (4)/ 3x8mm BCS	6496X
	(14)/ 3x6mm BCS (4)/ retainers (8)	0-100/1
8943	Suspension pin set, rear (left or right) (hardened steel), 4x64mm	6492X
0044	(1), 4x38mm (1), 4x33mm (1), 4x47mm (1)	
8941	Suspension pins, lower, inner (front or rear), 4x64mm (2) (hardened	6497
8940	steel) Suspension screw pin set, front or rear (hardened steel), 4x18mm (4),	6438
00-0	4x38mm (2), 4x33mm (2), 4x43mm (2)	6440
10295	Sway bar kit, Maxx Slash® (front and rear) (includes front and	6442
	rear sway bars and linkage)	6447R
10296	Sway bar set, Maxx Slash® (includes 1 each of all 5 sway bars)	

Shock Oil 031 Oil, shock (20 wt, 200 cSt, 60cc) (silicone) 032 Oil, shock (30 wt, 350 cSt, 60cc) (silicone) 033 Oil, shock (40 wt, 500 cSt, 60cc) (silicone) 034 Oil, shock (50 wt, 600 cSt, 60cc) (silicone) 035 Oil, shock (60 wt, 700 cSt, 60cc) (silicone) 036 Oil, shock (70 wt, 900 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone) 037 029 Shock oil bottle (60cc) (for mixing shock oil) 038X Shock oil set (includes 20 wt, 30 wt, 40 wt, 50 wt, 60 wt, 70 wt, & 80 wt premium shock oils with spinning carousel rack) 038 Spinning carousel rack Shocks (GT-Maxx®) 965X Body, GT-Maxx® shock (aluminum, blue-anodized) (1) 965G Body, GT-Maxx® shock (aluminum, green-anodized) (1) 965T Body, GT-Maxx® shock (aluminum, orange-anodized) (1) 965R Body, GT-Maxx® shock (aluminum, red-anodized) (1) Rebuild kit, GT-Maxx® shocks (lower cartridge, pistons, piston nuts, 962 bladders, screws) (renews 2 shocks) 964X Shock caps, aluminum (blue-anodized), GT-Maxx®, shocks (4) 964-GRAY Shock caps, aluminum (gray-anodized), GT-Maxx®, shocks (4) 964G Shock caps, aluminum (green-anodized), GT-Maxx® shocks (4) 964T Shock caps, aluminum (orange-anodized), GT-Maxx® shocks (4) 964R Shock caps, aluminum (red-anodized), GT-Maxx® shocks (4) Shock caps, GT-Maxx® shocks/ spring perch/ adjusters (2) (for 2 964 shocks) 963 Shock shaft, 72mm (GT-Maxx®) (steel, chrome finish) (2)/ rod ends (2)/ hollow balls (2) 963T Shock shaft, 72mm (GT-Maxx®) (TiN-coated) (2) (assembled with rod ends and steel hollow balls) 660 Shocks, GT-Maxx®, aluminum (blue-anodized) (fully assembled w/o springs) (2) 961G Shocks, GT-Maxx®, aluminum (green-anodized) (fully assembled w/o springs) (2) 961T Shocks, GT-Maxx®, aluminum (orange-anodized) (fully assembled w/o springs) (2) 961R Shocks, GT-Maxx®, aluminum (red-anodized) (fully assembled w/o springs) (2) 968X Spring retainer (adjuster), blue-anodized aluminum, GT-Maxx® shocks (4) (assembled with o-ring Spring retainer (adjuster), gray-anodized aluminum, GT-Maxx® 968-GRAY shocks (4) (assembled with o-ring Spring retainer (adjuster), green-anodized aluminum, GT-Maxx® 968G shocks (4) (assembled with o-ring) 968A Spring retainer (adjuster), orange-anodized aluminum, GT-Maxx® shocks (4) (assembled with o-ring) 968R Spring retainer (adjuster), red-anodized aluminum, GT-Maxx® shocks (4) (assembled with o-ring) 0240 Springs, shock (natural finish) (GT-Maxx®) (1.036 rate) (2) Springs, shock (natural finish) (GT-Maxx®) (1.150 rate, white stripe) 0241 (2)0242 Springs, shock (natural finish) (GT-Maxx®) (1.350 rate, brown stripe) (2) 0243 Springs, shock (natural finish) (GT-Maxx®) (1.400 rate, blue stripe) (2)Spur Gears & Pinion Gears 487X Gear, 15-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (for use only with steel spur gears) 489X Gear, 16-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (for use only with steel spur gears) 490X Gear, 17-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (for use only with steel spur gears) 491X Gear, 18-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (for use only with steel spur gears) 491R Gear, 18-T pinion (machined) (1.0 metric pitch) (fits 5mm shaft)/ set screw (for use only with steel spur gears) 494X Gear, 20-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (for use only with steel spur gears) 495X Gear, 22-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (for use only with steel spur gears) 496X Gear, 24-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (for use only with steel spur gears) 492X Gear, 25-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (for use only with steel spur gears) 497 Gear, 26-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw 438 Spur gear, 44-tooth (machined, hardened steel) (wide face) (1.0 metric pitch) 442 Spur gear, 46-tooth (machined, hardened steel) (wide face, 1.0 metric pitch)

Spur gear, 46-tooth, steel (wide-face, 1.0 metric pitch)

REV 240830.0833

### Page 5 Maxx® Slash®: TQi™ Traxxas Link™ Enabled 2.4GHz Radio & TSM® (Model 102076-4) Parts List

6443	Spur gear, 50-tooth (machined, hardened steel) (wide face, 1.0 metric pitch)	8940X	Suspension pin set, complete (hardened steel), 4x64mm (4), 4x22mm (4), 4x38mm (4), 4x33mm (4), 4x47mm (4)/ 3x8mm BCS
6448R <b>6444</b>	Spur gear, 50-tooth, steel (wide-face, 1.0 metric pitch) Spur gear, 54-tooth (machined, hardened steel) (wide face, 1.0	8942	(14)/ 3x6mm BCS (4)/ retainers (8) Suspension pin set, front (left or right) (hardened steel), 4x64mm
6449R	metric pitch) Spur gear, 54-tooth, steel (wide-face, 1.0 metric pitch)	8943	(1), 4x22mm (2), 4x38mm (1), 4x33mm (1), 4x47mm (1) Suspension pin set, rear (left or right) (hardened steel), 4x64mm
7020	Sigering Components Ball bearings, blue rubber sealed (8x12x3.5mm) (2)	8941	(1), 4x38mm (1), 4x33mm (1), 4x47mm (1) Suspension pins, lower, inner (front or rear), 4x64mm (2) (hardened steel)
10239-BLUE	Draglink, steering, 6061-T6 aluminum (blue-anodized) Draglink, steering, 6061-T6 aluminum (gray-anodized)	8940	Suspension screw pin set, front or rear (hardened steel), 4x18mm (4), 4x38mm (2), 4x33mm (2), 4x43mm (2)
10239-GRN		10295	Sway bar kit, Maxx Slash® (front and rear) (includes front and
10239-ORNG 10239-RED	Draglink, steering, 6061-T6 aluminum (orange-anodized) Draglink, steering, 6061-T6 aluminum (red-anodized)	10296	rear sway bars and linkage) Sway bar set, Maxx Slash® (includes 1 each of all 5 sway bars)
8947X	Servo horn, steel	8948X	Toe links, front (TUBES blue-anodized, 7075-T6 aluminum,
	Servo horn, steering, 6061-T6 aluminum (blue-anodized)/ 3x15mm BCS (with threadlock) (1)		stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1)
	Servo horn, steering, 6061-T6 aluminum (gray-anodized)/ 3x15mm BCS (with threadlock) (1)	8948-GRAY	Toe links, front (TUBES gray-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends,
10247-GRN	Servo horn, steering, 6061-T6 aluminum (green-anodized)/ 3x15mm BCS (with threadlock) (1)	8948G	front (4)/ aluminum wrench (1) Toe links, front (TUBES green-anodized, 7075-T6 aluminum,
10247-ORNG	Servo horn, steering, 6061-T6 aluminum (orange-anodized)/		stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1)
10247-RED	3x15mm BCS (with threadlock) (1) Servo horn, steering, 6061-T6 aluminum (red-anodized)/ 3x15mm	8948A	Toe links, front (TUBES orange-anodized, 7075-T6 aluminum,
8947	BCS (with threadlock) (1) Servo horn, steering/ linkage, steering (46mm, assembled with pivot		stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1)
	balls)	8948R	Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends,
10246-BLUE	Steering bellcranks, draglink (blue-anodized 6061-T6 aluminum)/ bellcrank bushing (1)/ 3x20mm BCS (with threadlock) (2)/		front (4)/ aluminum wrench (1)
	3x20mm BCS (with threadlock) (2)/ 3x20mm shoulder screws (with threadlock) (2)/ 3x15mm BCS (with threadlock) (1)/ 3x10mm	8948	Toe links, molded composite, 100mm (89mm center to center) (black) (2)
	CS (with threadlock) (1)		Team Traxxas Items
10246-GRAY	Steering bellcranks, draglink (gray-anodized 6061-T6 aluminum)/ bellcrank bushing (1)/ 3x20mm BCS (with threadlock) (2)/	2514	Decal sheet, racing sponsors
	3x20mm BCS (with threadlock) (2)/ 3x20mm shoulder screws	9950	Official Team Traxxas® racing decal set(flag logo/ 6-color)
	(with threadlock) (2)/ 3x15mm BCS (with threadlock) (1)/ 3x10mm CS (with threadlock) (1)	9909	Traxxas® racing banner, red & black (3x7 feet)
10246-GRN	Steering bellcranks, draglink (green-anodized 6061-T6	94474	Tires & Wheels
	aluminum)/ bellcrank bushing (1)/ 3x20mm BCS (with threadlock)	8447A	Nuts, 5mm flanged nylon locking (aluminum, black-anodized, serrated) (4)
	(2)/ 3x20mm BCS (with threadlock) (2)/ 3x20mm shoulder screws (with threadlock) (2)/ 3x15mm BCS (with threadlock) (1)/ 3x10mm	8447X	Nuts, 5mm flanged nylon locking (aluminum, blue-anodized,
10246-ORNG	CS (with threadlock) (1) Steering bellcranks, draglink (orange-anodized 6061-T6	8447G	serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, green-anodized,
10240-01110	aluminum)/ bellcrank bushing (1)/ 3x20mm BCS (with threadlock)	8447R	serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized,
	(2)/ 3x20mm BCS (with threadlock) (2)/ 3x20mm shoulder screws (with threadlock) (2)/ 3x15mm BCS (with threadlock) (1)/ 3x10mm		serrated) (4)
	CS (with threadlock) (1)	8447	Nuts, 5mm flanged nylon locking (steel, black serrated) (8)
10246-RED	Steering bellcranks, draglink (red-anodized 6061-T6 aluminum)/	8447 <b>5147X</b> 10272	Nuts, 5mm flanged nylon locking (steel, serrated) (8)
10246-RED	Steering bellcranks, draglink (red-anodized 6061-T6 aluminum)/ bellcrank bushing (1)/ 3x20mm BCS (with threadlock) (2)/ 3x20mm BCS (with threadlock) (2)/ 3x20mm shoulder screws	5147X	
10246-RED	Steering bellcranks, draglink (red-anodized 6061-T6 aluminum)/ bellcrank bushing (1)/ 3x20mm BCS (with threadlock) (2)/	5147X	Nuts, 5mm flanged nylon locking (steel, serrated) (8) Tires & wheels, assembled, glued, left (1), right (1) (black wheels,
<b>10246-RED</b> 8946	Steering bellcranks, draglink (red-anodized 6061-T6 aluminum)/ bellcrank bushing (1)/ 3x20mm BCS (with threadlock) (2)/ 3x20mm BCS (with threadlock) (2)/ 3x20mm shoulder screws (with threadlock) (2)/ 3x15mm BCS (with threadlock) (1)/ 3x10mm CS (with threadlock) (1) Steering bellcranks/ bellcrank support/ servo saver/ servo saver	<b>5147X</b> 10272	Nuts, 5mm flanged nylon locking (steel, serrated) (8) Tires & wheels, assembled, glued, left (1), right (1) (black wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires & wheels, assembled, glued, left (1), right (1) (black with satin beadlock wheels, Maxx Slash® belted tires, foam inserts)
	Steering bellcranks, draglink (red-anodized 6061-T6 aluminum)/ bellcrank bushing (1)/ 3x20mm BCS (with threadlock) (2)/ 3x20mm BCS (with threadlock) (2)/ 3x20mm shoulder screws (with threadlock) (2)/ 3x15mm BCS (with threadlock) (1)/ 3x10mm CS (with threadlock) (1)	<b>5147X</b> 10272 <b>10272-BLK</b>	Nuts, 5mm flanged nylon locking (steel, serrated) (8) Tires & wheels, assembled, glued, left (1), right (1) (black wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires & wheels, assembled, glued, left (1), right (1) (black with satin beadlock wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires & wheels, assembled, glued, left (1), right (1) (charcoal gray
8946	Steering bellcranks, draglink (red-anodized 6061-T6 aluminum)/ bellcrank bushing (1)/ 3x20mm BCS (with threadlock) (2)/ 3x20mm BCS (with threadlock) (2)/ 3x20mm shoulder screws (with threadlock) (2)/ 3x15mm BCS (with threadlock) (1)/ 3x10mm CS (with threadlock) (1) Steering bellcranks/ bellcrank support/ servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends,	<b>5147X</b> 10272 <b>10272-BLK</b>	Nuts, 5mm flanged nylon locking (steel, serrated) (8) Tires & wheels, assembled, glued, left (1), right (1) (black wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires & wheels, assembled, glued, left (1), right (1) (black with satin beadlock wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated)
8946	Steering bellcranks, draglink (red-anodized 6061-T6 aluminum)/ bellcrank bushing (1)/ 3x20mm BCS (with threadlock) (2)/ 3x20mm BCS (with threadlock) (2)/ 3x20mm shoulder screws (with threadlock) (2)/ 3x15mm BCS (with threadlock) (1)/ 3x10mm CS (with threadlock) (1) Steering bellcranks/ bellcrank support/ servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES gray-anodized, 7075-T6 aluminum,	<b>5147X</b> 10272 <b>10272-BLK</b> <b>10272-GRAY</b> 10270	Nuts, 5mm flanged nylon locking (steel, serrated) (8) Tires & wheels, assembled, glued, left (1), right (1) (black wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires & wheels, assembled, glued, left (1), right (1) (black with satin beadlock wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires & wheels, assembled, glued, left (1), right (1) (charcoal gray wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires, Maxx Slash® (belted) (2)/ foam inserts (2)
8946 <b>8948X</b>	Steering bellcranks, draglink (red-anodized 6061-T6 aluminum)/ bellcrank bushing (1)/ 3x20mm BCS (with threadlock) (2)/ 3x20mm BCS (with threadlock) (2)/ 3x20mm shoulder screws (with threadlock) (2)/ 3x15mm BCS (with threadlock) (1)/ 3x10mm CS (with threadlock) (1) Steering bellcranks/ bellcrank support/ servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES gray-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends,	<b>5147X</b> 10272- <b>BLK</b> <b>10272-GRAY</b> 10270 8956	Nuts, 5mm flanged nylon locking (steel, serrated) (8) Tires & wheels, assembled, glued, left (1), right (1) (black wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires & wheels, assembled, glued, left (1), right (1) (black with satin beadlock wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires & wheels, assembled, glued, left (1), right (1) (charcoal gray wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires, Maxx Slash® (belted) (2)/ foam inserts (2) Wheel hubs, hex (2)/ 2.5x14 pins (2)
8946 <b>8948X</b>	Steering bellcranks, draglink (red-anodized 6061-T6 aluminum)/ bellcrank bushing (1)/ 3x20mm BCS (with threadlock) (2)/ 3x20mm BCS (with threadlock) (2)/ 3x20mm shoulder screws (with threadlock) (2)/ 3x15mm BCS (with threadlock) (1)/ 3x10mm CS (with threadlock) (1) Steering bellcranks/ bellcrank support/ servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES gray-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES green-anodized, 7075-T6 aluminum,	<b>5147X</b> 10272-BLK <b>10272-BLK</b> <b>10272-GRAY</b> 10270 8956 <b>8956X</b>	Nuts, 5mm flanged nylon locking (steel, serrated) (8) Tires & wheels, assembled, glued, left (1), right (1) (black wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires & wheels, assembled, glued, left (1), right (1) (black with satin beadlock wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires & wheels, assembled, glued, left (1), right (1) (charcoal gray wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires, Maxx Slash® (belted) (2)/ foam inserts (2) Wheel hubs, hex, aluminum (blue-anodized) (4)/ 4x13mm screw pins (4)
8946 8948X 8948-GRAY	Steering bellcranks, draglink (red-anodized 6061-T6 aluminum)/ bellcrank bushing (1)/ 3x20mm BCS (with threadlock) (2)/ 3x20mm BCS (with threadlock) (2)/ 3x20mm shoulder screws (with threadlock) (2)/ 3x15mm BCS (with threadlock) (1)/ 3x10mm CS (with threadlock) (1) Steering bellcranks/ bellcrank support/ servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES gray-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1)	<b>5147X</b> 10272- <b>BLK</b> <b>10272-GRAY</b> 10270 8956	Nuts, 5mm flanged nylon locking (steel, serrated) (8) Tires & wheels, assembled, glued, left (1), right (1) (black wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires & wheels, assembled, glued, left (1), right (1) (black with satin beadlock wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires & wheels, assembled, glued, left (1), right (1) (charcoal gray wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires, Maxx Slash® (belted) (2)/ foam inserts (2) Wheel hubs, hex, (2)/ 2.5x14 pins (2) Wheel hubs, hex, aluminum (blue-anodized) (4)/ 4x13mm screw
8946 8948X 8948-GRAY	Steering bellcranks, draglink (red-anodized 6061-T6 aluminum)/ bellcrank bushing (1)/ 3x20mm BCS (with threadlock) (2)/ 3x20mm BCS (with threadlock) (2)/ 3x20mm shoulder screws (with threadlock) (2)/ 3x15mm BCS (with threadlock) (1)/ 3x10mm CS (with threadlock) (1) Steering bellcranks/ bellcrank support/ servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES gray-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1)	<b>5147X</b> 10272-BLK <b>10272-BLK</b> <b>10272-GRAY</b> 10270 8956 <b>8956X</b>	Nuts, 5mm flanged nylon locking (steel, serrated) (8) Tires & wheels, assembled, glued, left (1), right (1) (black wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires & wheels, assembled, glued, left (1), right (1) (black with satin beadlock wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires & wheels, assembled, glued, left (1), right (1) (charcoal gray wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires, Maxx Slash® (belted) (2)/ foam inserts (2) Wheel hubs, hex, aluminum (blue-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, hex, aluminum (green-anodized) (4)/ 4x13mm
8946 8948X 8948-GRAY 8948G 8948A	Steering bellcranks, draglink (red-anodized 6061-T6 aluminum)/ bellcrank bushing (1)/ 3x20mm BCS (with threadlock) (2)/ 3x20mm BCS (with threadlock) (2)/ 3x20mm shoulder screws (with threadlock) (2)/ 3x15mm BCS (with threadlock) (1)/ 3x10mm CS (with threadlock) (1) Steering bellcranks/ bellcrank support/ servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES gray-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES orange-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES orange-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1)	<b>5147X</b> 10272-BLK <b>10272-GRAY</b> 10270 8956 <b>8956X</b> <b>8956G</b>	Nuts, 5mm flanged nylon locking (steel, serrated) (8) Tires & wheels, assembled, glued, left (1), right (1) (black wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires & wheels, assembled, glued, left (1), right (1) (black with satin beadlock wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires & wheels, assembled, glued, left (1), right (1) (charcoal gray wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires, Maxx Slash® (belted) (2)/ foam inserts (2) Wheel hubs, hex, (2)/ 2.5x14 pins (2) Wheel hubs, hex, aluminum (blue-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, hex, aluminum (orange-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, hex, aluminum (red-anodized) (4)/ 4x13mm screw
8946 8948X 8948-GRAY 8948G	Steering bellcranks, draglink (red-anodized 6061-T6 aluminum)/ bellcrank bushing (1)/ 3x20mm BCS (with threadlock) (2)/ 3x20mm BCS (with threadlock) (2)/ 3x20mm shoulder screws (with threadlock) (2)/ 3x15mm BCS (with threadlock) (1)/ 3x10mm CS (with threadlock) (1) Steering bellcranks/ bellcrank support/ servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES gray-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES orange-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES orange-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1)	5147X 10272 10272-BLK 10272-GRAY 10270 8956 89565 8956G 8956G	Nuts, 5mm flanged nylon locking (steel, serrated) (8) Tires & wheels, assembled, glued, left (1), right (1) (black wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires & wheels, assembled, glued, left (1), right (1) (black with satin beadlock wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires & wheels, assembled, glued, left (1), right (1) (charcoal gray wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires, Maxx Slash® (belted) (2)/ foam inserts (2) Wheel hubs, hex (2)/ 2.5x14 pins (2) Wheel hubs, hex, aluminum (blue-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, hex, aluminum (orange-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, hex, aluminum (red-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, hex, aluminum (red-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, splined, 17mm (blue-anodized) (4)/ 4x5 GS (4),
8946 8948X 8948-GRAY 8948G 8948A	Steering bellcranks, draglink (red-anodized 6061-T6 aluminum)/ bellcrank bushing (1)/ 3x20mm BCS (with threadlock) (2)/ 3x20mm BCS (with threadlock) (2)/ 3x20mm shoulder screws (with threadlock) (2)/ 3x15mm BCS (with threadlock) (1)/ 3x10mm CS (with threadlock) (1) Steering bellcranks/ bellcrank support/ servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES gray-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES orange-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, molded composite, 100mm (89mm center to center) (black)	5147X 10272 10272-BLK 10272-GRAY 10270 8956 8956G 8956G 8956G 8956F 8956R 8956R	Nuts, 5mm flanged nylon locking (steel, serrated) (8) Tires & wheels, assembled, glued, left (1), right (1) (black wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires & wheels, assembled, glued, left (1), right (1) (black with satin beadlock wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires & wheels, assembled, glued, left (1), right (1) (charcoal gray wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires, Maxx Slash® (belted) (2)/ foam inserts (2) Wheel hubs, hex, 2)/ 2.5x14 pins (2) Wheel hubs, hex, aluminum (blue-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, hex, aluminum (orange-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, hex, aluminum (red-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, hex, aluminum (red-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, splined, 17mm (blue-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (gray-anodized) (4)/ 4x5 GS (4),
8946 8948X 8948-GRAY 8948G 8948A 8948R	Steering bellcranks, draglink (red-anodized 6061-T6 aluminum)/ bellcrank bushing (1)/ 3x20mm BCS (with threadlock) (2)/ 3x20mm BCS (with threadlock) (2)/ 3x20mm shoulder screws (with threadlock) (2)/ 3x15mm BCS (with threadlock) (1)/ 3x10mm CS (with threadlock) (1) Steering bellcranks/ bellcrank support/ servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES gray-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES orange-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES orange-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES orange-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES orange-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, molded composite, 100mm (89mm center to center) (black) (2)	5147X 10272 10272-BLK 10272-GRAY 10270 8956 8956G 8956G 8956G 8956F 8956R 8956R	Nuts, 5mm flanged nylon locking (steel, serrated) (8) Tires & wheels, assembled, glued, left (1), right (1) (black wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires & wheels, assembled, glued, left (1), right (1) (black with satin beadlock wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires & wheels, assembled, glued, left (1), right (1) (charcoal gray wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires, Maxx Slash® (belted) (2)/ foam inserts (2) Wheel hubs, hex, aluminum (blue-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, hex, aluminum (green-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, hex, aluminum (red-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, hex, aluminum (red-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, splined, 17mm (blue-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4)
8946 8948X 8948-GRAY 8948G 8948A 8948R 8948 8948	Steering bellcranks, draglink (red-anodized 6061-T6 aluminum)/ bellcrank bushing (1)/ 3x20mm BCS (with threadlock) (2)/ 3x20mm BCS (with threadlock) (2)/ 3x20mm shoulder screws (with threadlock) (2)/ 3x15mm BCS (with threadlock) (1)/ 3x10mm CS (with threadlock) (1) Steering bellcranks/ bellcrank support/ servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES gray-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES orange-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, molded composite, 100mm (89mm center to center) (black) (2) SISICENSION Link(ALGE Linkage, sway bar (front or rear)	5147X 10272 10272-BLK 10272-GRAY 10270 8956 8956C 8956G 8956G 8956F 8956R 8654 8654-GRAY 8654G	Nuts, 5mm flanged nylon locking (steel, serrated) (8) Tires & wheels, assembled, glued, left (1), right (1) (black wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires & wheels, assembled, glued, left (1), right (1) (black with satin beadlock wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires & wheels, assembled, glued, left (1), right (1) (charcoal gray wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires, Maxx Slash® (belted) (2)/ foam inserts (2) Wheel hubs, hex, 2)/ 2.5x14 pins (2) Wheel hubs, hex, aluminum (blue-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, hex, aluminum (green-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, hex, aluminum (red-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, splined, 17mm (blue-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (green-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4)
8946 8948X 8948-GRAY 8948G 8948A 8948A 8948R 8948	Steering bellcranks, draglink (red-anodized 6061-T6 aluminum)/ bellcrank bushing (1)/ 3x20mm BCS (with threadlock) (2)/ 3x20mm BCS (with threadlock) (2)/ 3x20mm shoulder screws (with threadlock) (2)/ 3x15mm BCS (with threadlock) (1)/ 3x10mm CS (with threadlock) (1) Steering bellcranks/ bellcrank support/ servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES gray-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES orange-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, molded composite, 100mm (89mm center to center) (black) (2) <b>SUSICENTIALITICAGE</b> Linkage, sway bar (front or rear) Mounts, sway bar (front or rear)	5147X 10272 10272-BLK 10272-GRAY 10270 8956 8956G 8956G 8956G 8956F 8956R 8654 8654-GRAY 8654G 8654A	Nuts, 5mm flanged nylon locking (steel, serrated) (8) Tires & wheels, assembled, glued, left (1), right (1) (black wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires & wheels, assembled, glued, left (1), right (1) (black with satin beadlock wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires & wheels, assembled, glued, left (1), right (1) (charcoal gray wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires, Maxx Slash® (belted) (2)/ foam inserts (2) Wheel hubs, hex, aluminum (blue-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, hex, aluminum (green-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, hex, aluminum (red-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, splined, 17mm (blue-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (green-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (green-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (green-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (green-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (green-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (green-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (green-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4)
8946 8948X 8948-GRAY 8948G 8948A 8948R 8948 8948	Steering bellcranks, draglink (red-anodized 6061-T6 aluminum)/ bellcrank bushing (1)/ 3x20mm BCS (with threadlock) (2)/ 3x20mm BCS (with threadlock) (2)/ 3x15mm BCS (with threadlock) (1)/ 3x20mm BCS (with threadlock) (1) Steering bellcranks/ bellcrank support/ servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES gray-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES gray-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES orange-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES orange-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, molded composite, 100mm (89mm center to center) (black) (2) <b>SUS1)ELISION LINK(1)E</b> Kad ends (4) (assembled with steel pivot balls) (replacement ends for #8547A, 8547R, 8547X, 8948A, 8948G, 8948R, 8948X,	5147X 10272 10272-BLK 10272-GRAY 10270 8956 8956C 8956G 8956G 8956F 8956R 8654 8654-GRAY 8654G	Nuts, 5mm flanged nylon locking (steel, serrated) (8) Tires & wheels, assembled, glued, left (1), right (1) (black wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires & wheels, assembled, glued, left (1), right (1) (black with satin beadlock wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires & wheels, assembled, glued, left (1), right (1) (charcoal gray wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires, Maxx Slash® (belted) (2)/ foam inserts (2) Wheel hubs, hex, (2)/ 2.5x14 pins (2) Wheel hubs, hex, aluminum (blue-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, hex, aluminum (green-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, hex, aluminum (red-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, splined, 17mm (blue-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (green-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (green-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (orange-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (orange-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (orange-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (orange-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (orange-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (orange-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (orange-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (orange-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (orange-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (orange-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (orange-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (orange-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4)
8946 8948X 8948-GRAY 8948G 8948A 8948R 8948R 8948 10298 10297 8958	Steering bellcranks, draglink (red-anodized 6061-T6 aluminum)/ bellcrank bushing (1)/ 3x20mm BCS (with threadlock) (2)/ 3x20mm BCS (with threadlock) (2)/ 3x20mm shoulder screws (with threadlock) (2)/ 3x15mm BCS (with threadlock) (1)/ 3x10mm CS (with threadlock) (1) Steering bellcranks/ bellcrank support/ servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES gray-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES orange-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES orange-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, molded composite, 100mm (89mm center to center) (black) (2) <b>SUSICENSION LINKAGE</b> Linkage, sway bar (front or rear) Mounts, sway bar (front and rear)/ 3x6mm FCS (4) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #8547A, 8547R, 8547X, 8948A, 8948G, 8948R, 8948X, 8997A, 8997G, 8997R, 8997X)	5147X 10272 10272-BLK 10272-GRAY 10270 8956 8956G 8956G 8956T 8956R 8654 8654-GRAY 8654G 8654A 8654A 8654R	Nuts, 5mm flanged nylon locking (steel, serrated) (8) Tires & wheels, assembled, glued, left (1), right (1) (black wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires & wheels, assembled, glued, left (1), right (1) (black with satin beadlock wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires & wheels, assembled, glued, left (1), right (1) (charcoal gray wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires, Maxx Slash® (belted) (2)/ foam inserts (2) Wheel hubs, hex (2)/ 2.5x14 pins (2) Wheel hubs, hex, aluminum (blue-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, hex, aluminum (green-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, hex, aluminum (red-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, splined, 17mm (blue-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (grey-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (green-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (green-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (green-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (green-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (green-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (green-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4)
8946 8948X 8948-GRAY 8948G 8948A 8948A 8948R 8948	Steering bellcranks, draglink (red-anodized 6061-T6 aluminum)/ bellcrank bushing (1)/ 3x20mm BCS (with threadlock) (2)/ 3x20mm BCS (with threadlock) (2)/ 3x15mm BCS (with threadlock) (1)/ 3x20mm BCS (with threadlock) (1) Steering bellcranks/ bellcrank support/ servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES gray-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES gray-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES orange-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES orange-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, molded composite, 100mm (89mm center to center) (black) (2) <b>SUS1)ELISION LINK(1)E</b> Kad ends (4) (assembled with steel pivot balls) (replacement ends for #8547A, 8547R, 8547X, 8948A, 8948G, 8948R, 8948X,	5147X 10272 10272-BLK 10272-GRAY 10270 8956 8956G 8956G 8956G 8956F 8654G 8654G 8654G 8654G 8654A 8654A 8654A	Nuts, 5mm flanged nylon locking (steel, serrated) (8) Tires & wheels, assembled, glued, left (1), right (1) (black wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires & wheels, assembled, glued, left (1), right (1) (black with satin beadlock wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires & wheels, assembled, glued, left (1), right (1) (charcoal gray wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires, Maxx Slash® (belted) (2)/ foam inserts (2) Wheel hubs, hex, (2)/ 2.5x14 pins (2) Wheel hubs, hex, aluminum (blue-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, hex, aluminum (green-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, hex, aluminum (red-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, splined, 17mm (blue-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (gray-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (green-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (green-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (green-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (red-an
8946 8948X 8948-GRAY 8948G 8948A 8948A 8948R 8948 10298 10297 8958 7743-BLUE 7743-GRAY	Steering bellcranks, draglink (red-anodized 6061-T6 aluminum)/ bellcrank bushing (1)/ 3x20mm BCS (with threadlock) (2)/ 3x20mm BCS (with threadlock) (2)/ 3x20mm shoulder screws (with threadlock) (2)/ 3x15mm BCS (with threadlock) (1)/ 3x10mm CS (with threadlock) (1) Steering bellcranks/ bellcrank support/ servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES gray-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES orange-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, molded composite, 100mm (89mm center to center) (black) (2) <b>SIISIENTINIALIANS</b> (a) <b>SIISIENTINIALIANS</b> (a) assembled with steel pivot balls) (replacement ends for #8547A, 8547R, 8547R, 8947A, 8948A, 8948A, 8948G, 8948R, 8948X, 8997A, 8997G, 8997R, 8997X) Suspension pin retainer (4) Suspension pin retainer (4) Suspension pin retainer, 6061-T6 aluminum (gray-anodized) (4) Suspension pin retainer, 6061-T6 aluminum (gray-anodized) (4)	5147X 10272 10272-BLK 10272-GRAY 10270 8956 8956G 8956G 8956T 8956R 8654 8654-GRAY 8654G 8654A 8654A 8654R	Nuts, 5mm flanged nylon locking (steel, serrated) (8) Tires & wheels, assembled, glued, left (1), right (1) (black wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires & wheels, assembled, glued, left (1), right (1) (black with satin beadlock wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires & wheels, assembled, glued, left (1), right (1) (charcoal gray wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires, Maxx Slash® (belted) (2)/ foam inserts (2) Wheel hubs, hex, (2)/ 2.5x14 pins (2) Wheel hubs, hex, aluminum (blue-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, hex, aluminum (green-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, hex, aluminum (red-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, splined, 17mm (blue-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (gray-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (green-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (green-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (green-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel washers (4) Wheel washers (4) Wheel washers (4) Wheel washers (4)
8946 8948X 8948-GRAY 8948G 8948A 8948A 8948R 8948 10298 10297 8958 7743-BLUE 7743-GRAY 7743-GRN	Steering bellcranks, draglink (red-anodized 6061-T6 aluminum)/ bellcrank bushing (1)/ 3x20mm BCS (with threadlock) (2)/ 3x20mm BCS (with threadlock) (2)/ 3x15mm BCS (with threadlock) (1)/ 3x20mm BCS (with threadlock) (1) Steering bellcranks/ bellcrank support/ servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES gray-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES orange-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, molted composite, 100mm (89mm center to center) (black) (2) <b>SISIGISIOI Link(2)G</b> Linkage, sway bar (front or rear) Mounts, sway bar (front or rear) Mounts, sway bar (front and rear)/ 3x6mm FCS (4) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #8547A, 8547R, 8547X, 8948A, 8948G, 8948R, 8948X, 8997A, 8997G, 8997R, 8997X) Suspension pin retainer (4) Suspension pin retainer, 6061-T6 aluminum (gray-anodized) (4) Suspension pin retainer, 6061-T6 aluminum (green-anodized) (4)	5147X 10272 10272-BLK 10272-GRAY 10270 8956 8956G 8956G 8956G 8956G 8956G 86544 86544 86544 86544 86544 86544 86544 86557 8757 8757 8757 8757 8757 8757 875	Nuts, 5mm flanged nylon locking (steel, serrated) (8) Tires & wheels, assembled, glued, left (1), right (1) (black wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires & wheels, assembled, glued, left (1), right (1) (black with satin beadlock wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires & wheels, assembled, glued, left (1), right (1) (charcoal gray wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires, Maxx Slash® (belted) (2)/ foam inserts (2) Wheel hubs, hex, 2)/ 2.5x14 pins (2) Wheel hubs, hex, aluminum (blue-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, hex, aluminum (green-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, hex, aluminum (red-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, splined, 17mm (blue-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (gray-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (green-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (green-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (orange-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel washers (4) Wheel washers (4) Wheel washers (4) Wheel washers (4) Wheel washers, blue (4) Wheel washers, spreen (4) Wheel washers, machined aluminum, blue (4)
8946 8948X 8948-GRAY 8948G 8948A 8948A 8948R 8948 10298 10297 8958 7743-BLUE 7743-GRAY	Steering bellcranks, draglink (red-anodized 6061-T6 aluminum)/ bellcrank bushing (1)/ 3x20mm BCS (with threadlock) (2)/ 3x20mm BCS (with threadlock) (2)/ 3x15mm BCS (with threadlock) (1)/ 3x20mm BCS (with threadlock) (1) Steering bellcranks/ bellcrank support/ servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES gray-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES orange-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, molted composite, 100mm (89mm center to center) (black) (2) <b>SISIGISIOI Link(2)G</b> Linkage, sway bar (front or rear) Mounts, sway bar (front or rear) Mounts, sway bar (front and rear)/ 3x6mm FCS (4) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #8547A, 8547R, 8547X, 8948A, 8948G, 8948R, 8948X, 8997A, 8997G, 8997R, 8997X) Suspension pin retainer (4) Suspension pin retainer, 6061-T6 aluminum (gray-anodized) (4) Suspension pin retainer, 6061-T6 aluminum (green-anodized) (4)	5147X 10272 10272-BLK 10272-GRAY 10270 8956 8956G 8956G 8956G 8956G 8956G 86544 86544 86544 86544 86544 86544 86544 88957 10257 8957X 89575 10257-BLUE 10257-GRAY	Nuts, 5mm flanged nylon locking (steel, serrated) (8) Tires & wheels, assembled, glued, left (1), right (1) (black wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires & wheels, assembled, glued, left (1), right (1) (black with satin beadlock wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires & wheels, assembled, glued, left (1), right (1) (charcoal gray wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires, Maxx Slash® (belted) (2)/ foam inserts (2) Wheel hubs, hex (2)/ 2.5x14 pins (2) Wheel hubs, hex, aluminum (blue-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, hex, aluminum (green-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, hex, aluminum (orange-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, hex, aluminum (red-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, splined, 17mm (blue-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (grey-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (green-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (orange-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (orange-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel washers (4) Wheel washers (4) Wheel washers (4) Wheel washers (4) Wheel washers, blue (4) Wheel washers, sgreen (4) Wheel washers, machined aluminum, blue (4) Wheel washers, machined aluminum, gray (4)
8946 8948X 8948-GRAY 8948G 8948A 8948A 8948R 8948 10298 10297 8958 7743-BLUE 7743-GRAY 7743-GRN	Steering bellcranks, draglink (red-anodized 6061-T6 aluminum)/ bellcrank bushing (1)/ 3x20mm BCS (with threadlock) (2)/ 3x20mm BCS (with threadlock) (2)/ 3x15mm BCS (with threadlock) (1)/ Steering bellcranks/ bellcrank support/ servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES gray-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES orange-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES orange-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) Toe links, molded composite, 100mm (89mm center to center) (black) (2) <b>SISIENTINA (1)</b> Mounts, sway bar (front or rear) Mounts, sway bar (front and rear)/ 3x6mm FCS (4) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #8547A, 8547R, 8547X, 8948A, 8948G, 8948R, 8948X, 8997A, 8997G, 8997R, 8997X) Suspension pin retainer (4) Suspension pin retainer, 6061-T6 aluminum (gray-anodized) (4)	5147X 10272 10272-BLK 10272-GRAY 10270 8956 8956G 8956G 8956G 8956G 8956G 86544 86544 86544 86544 86544 86544 86544 86557 8757 8757 8757 8757 8757 8757 875	Nuts, 5mm flanged nylon locking (steel, serrated) (8) Tires & wheels, assembled, glued, left (1), right (1) (black wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires & wheels, assembled, glued, left (1), right (1) (black with satin beadlock wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires & wheels, assembled, glued, left (1), right (1) (charcoal gray wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) Tires, Maxx Slash® (belted) (2)/ foam inserts (2) Wheel hubs, hex, 2)/ 2.5x14 pins (2) Wheel hubs, hex, aluminum (blue-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, hex, aluminum (green-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, hex, aluminum (orange-anodized) (4)/ 4x13mm screw pins (4) Wheel hubs, splined, 17mm (blue-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (grey-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (green-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (orange-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (orange-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (orange-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel washers (4) Wheel washers (4) Wheel washers (4) Wheel washers, blue (4) Wheel washers, spreen (4) Wheel washers, machined aluminum, blue (4)

### Page 6 Maxx® Slash®: TQi™ Traxxas Link™ Enabled 2.4GHz Radio & TSM® (Model 102076-4) Parts List

	Wheel washers, machined aluminum, orange (4)
10257-RED	Wheel washers, machined aluminum, red (4)
8957T 8957R	Wheel washers, orange (4) Wheel washers, red (4)
10271	Wheels (black) (2)
10211	Transmission Components
10287 BLUE	Cover, gear (blue-anodized 6061-T6 aluminum)
	Cover, gear (gray-anodized 6061-16 aluminum)
10287-GRN	Cover, gear (green-anodized 6061-T6 aluminum)
10287-ORNG	Cover, gear (orange-anodized 6061-T6 aluminum)
10287-RED	Cover, gear (red-anodized 6061-T6 aluminum)
8987	Covers, gear (2)
8985 8986	Input gear, transmission, 22-tooth/ 2.5x12mm pin Input shaft, transmission
5040	Oil, differential (20M wt) (standard)
	Traxxas Tools
3433X	Body reamer (aluminum handle)
3433	Body reamer (plastic handle)
3436	Cap, body reamer
3432	Scissors, curved tip
3431	Scissors, straight tip
8712	Speed Bit Essentials Set, hex and nut driver, 7-piece, includes premium handle (medium), travel pouch, hex drivers (straight:
	1.5mm, 2.0mm, 2.5mm) and nut drivers (5.0mm, 5.5mm, 7.0mm,
	and 8.0mm), 1/4" drive
8720	Speed bit handle, large (overmolded)
8721	Speed bit handle, medium (one piece)
8722 8710	Speed bit handle, premium (rubber overmold) Speed Bit Master Set, hex and nut driver, 13-piece, includes
0/10	premium handle (medium), travel pouch, hex drivers (straight:
	1.5mm, 2.0mm, 2.5mm, 3.0mm), (ball-end: 2.0mm, 2.5mm,
	3.0mm), and nut drivers (4.0mm, 4.5mm, 5.0mm, 5.5mm, 7.0mm,
8711	8.0mm), 1/4" drive Speed Bit Master Set, hex driver, 7-piece straight and ball end,
0.11	includes premium handle (medium), travel pouch, hex drivers
	(straight: 1.5mm, 2.0mm, 2.5mm, 3.0mm) (ball end: 2.0mm,
8719	2.5mm, 3.0mm), 1/4" drive
0/19	Speed Bit Master Set, nut driver, 6-piece, includes premium handle (medium), travel pouch, and nut drivers (4.0mm, 4.5mm,
	5.0mm, 5.5mm, 7.0mm, 8.0mm), 1/4" drive
8716	Speed Bit Set, hex driver, 2-piece ball-end (2.0mm, 2.5mm), 1/4"
8716X	drive Speed Bit Set, hex driver, 3-piece ball-end (2.0mm, 2.5mm,
0/10	3.0mm) 1/4" drive
8715	Speed Bit Set, hex driver, 3-piece straight (1.5mm, 2.0mm,
	2.5mm), 1/4" drive
8715X	Speed Bit Set, hex driver, 4-piece straight (1.5mm, 2.0mm, 2.5mm, 3.0mm), 1/4" drive
8714	Speed Bit Set, screwdriver, 3-piece straight (3mm slotted, #1
	Phillips, and #2 Phillips bits), 1/4" drive
2748R	Tool set (includes 1.5mm hex wrench / 2.0mm hex wrench /
	2.5mm hex wrench/ 4-way wrench/ 8mm & 4mm wrench/ U-joint wrench)
3415	Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm,
	3.5mm, 4mm drivers/4mm. 5mm, 5.5mm, 7mm, and 8mm nut
	drivers/ 2mm, 3mm, and 4mm slotted screwdrivers/ #00 Phillips,
	#0 Phillips, and #1 Phillips screwdrivers/ 4mm and 8mm wrenches/ driver handle)
	Turnbuckles & Threaded Rods
90497	
8948X	Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends,
	front (4)/ aluminum wrench (1)
8948-GRAY	Toe links, front (TUBES gray-anodized, 7075-T6 aluminum,
	stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1)
8948G	Toe links, front (TUBES green-anodized, 7075-T6 aluminum,
	stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends,
	front (4)/ aluminum wrench (1)
8948A	Toe links, front (TUBES orange-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends,
	front (4)/ aluminum wrench (1)
8948R	Toe links, front (TUBES red-anodized, 7075-T6 aluminum,
	stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends,
8948	front (4)/ aluminum wrench (1) Toe links, molded composite, 100mm (89mm center to center) (black)
0340	(2)
	x /

If you have questions or need technical assistance, call Traxxas at:

## 1-888-TRAXXAS

(1-888-872-9927) (U.S. residents only)

For orders, calls outside the U.S., and other information, call 972-549-3000, or fax to 972-549-3011 e-mail Traxxas at support@Traxxas.com TRAXXAS.COM